

Bull Plugs

WNS Lowery Bull Plugs provide a simple and proven method of closing a threaded hole or sealing the end of a line of pipe. Our Bull Plugs can be used as an isolation device in piping systems, conduits, or wellbore tubulars. Bull Plugs can be removed during line maintenance operations to drain fluids from the system. The ½" NPT optional tap allows for use with pressure gauges, automatic shutdown devices, or other equipment.

Features:

- Solid or ½" NPT tapped options available
- Standard Sizes available
- API and NPT/LP connection styles
- Standard, XH, and XXH wall thickness options

Applications:

- Artificial Lift Wellheads

Part Numbers:

Connection and Weight	Part Number
2 3/8"-8RD, STD	302079
2 3/8"-8RD, XH	30644
2 3/8"-8RD, XXH	302132
2 3/8"-8RD, STD, ½" NPT Tap	302136
2 3/8"-8RD, XH, ½" NPT Tap	302136
2 3/8"-8RD, XXH, ½" NPT Tap	302133
2 7/8"-8RD, STD	302078
2 7/8"-8RD, XH	30645
2 7/8"-8RD, XXH	302216
2 7/8"-8RD, STD, ½" NPT Tap	302137
2 7/8"-8RD, XH, ½" NPT Tap	302120
2 7/8"-8RD, XXH, ½" NPT Tap	302221
3 1/2"-8RD, XH	302089
3 1/2"-8RD, XXH, ½" NPT Tap	302180
4 1/2"-8RD, STD, ½" NPT Tap	302095
2"-11 ½ NPT, STD	302080

*More options available upon request

